



www.growland.net / www.growland-hydroponics.com
<https://www.growland.fr> / <https://www.growland.co.uk>
<https://www.growland.es> / <https://www.growland.at>
<https://www.growland.nl> / <https://www.growland.it>
<https://www.growland.se> / <https://www.growland.pl>

SL.600W.U46.DSP

SUNMASTER® High Pressure Sodium Lamp E40 Tubular

Lamp Type	Sunmaster Grow Lamps
Product Number	10036
Control Gear	HPS Ballast + Ignitor / Electronic

Performance Data

Initial Lumens (Lumens @ 100 hours)	90000
PAR Watts	215
Rated Life (Hrs. @10Hr. /Start)	24000+
Correlated Colour Temperature K	2000
Chromaticity (CIE - X,Y)	530 425
Colour Rendering Index (CRI)	25
Typical Warm Up Time (Minutes)	3-5
Typical Hot Restart Time (Minutes)	1
Burning Position	Universal

Physical Data / Requirements

Base Designation	E40
Bulb Designation	T46
Bulb Diameter (mm)	46
Max. Overall Length (mm)	285
Light Centre Length (mm)	175
Effective Arc Length (mm)	125
Max. Base Temperature (°C)	250
Max. Bulb Temperature (°C)	400
Luminaire Type	Open/Enclosed
Socket Pulse Rating (KV)	5

Electrical Data / Requirements

Lamp Wattage (W)	600
Operating Voltage (V)	115
Operating Current (Amps)	5.8
Min. Open Circuit Voltage (RMS)	198
Min.-Max. Starting Pulse (Peak V)	3800 - 4500
Min. Pulse Width @ 2700 Volts (µ sec)	1
Min. Pulse Rate Per ½ Cycle	1
Pulse Position (Min. % OCV Peak)	60-90, 240-270

Revision:

Notes

The specification contains data about typical performance on 50Hz sine wave ballast at nominal power. Actual values may depend on ballast and applications.

Complies with (CE), Low Voltage (CE), WEEE and RoHS Directives.